ARRISUN 12 Plus Description

ARRISUN 12 Plus

ARRISUN
Together with the Compact range, the ARRISUN is the working horse on location. Whenever punch or bounce light is required on a set, an ARRISUN is the ultimate answer. For the first time the interaction of lamp, reflector and converter lens was taken into consideration and computer simulated, resulting in unmatched light performance. A wide range of converter lenses ensure maximum beam control in all situations.



ARRISUN 12 Plus Technical Data

ARRISUN 12 Plus

Measurement: ▸ Metric (m/lx) ▸ US Units (ft/fc)

Type of Lamphead:	Par
Power:	1200 W
Lamp Type:	HMI 1200 W/SE G38 show_all
Supply Voltage:	100 V
Correlated Color Temperature:	6000 K
Lamp Base:	G38
Lens Diameter:	250 mm
Barn Door Size:	344 mm
Filter Insertion Size:	335 mm
Mounting:	Spigot 28mm
Packed Size:	530 mm - 530 mm - 620 mm
Packed Volume:	174160 ccm
Shipping Weight:	15 kg
Protection Class:	IP 23
Compliance:	CE

ARRISUN 12 Plus

Description:

- Magnetic Ballast 1,2 kW, 230/240 V
- Magnetic Ballast 1,2 kW, 230/240 V
- Electronic Ballast EB 575/1200 W
- Electronic Ballast EB 575/1200 W
- Electronic Ballast EBB 575/1200 W 24- 60 VDC (575W), 48-60 VDC (1200W)
- Electronic Ballast EBB 575/1200 W 24- 60 VDC (575W), 48-60 VDC (1200W)
- 4-Leaf Barndoor, rotateable, 344 mm
- Scrim Set, 330 mm
- Spot Lens 9°
- Narrow Flood-Lens 10°x20°
- Flood Lens 20°x40°
- Super Flood-Lens 58°
- Super Flood-Lens, Frosted
- Head/Ballast Cable 575/1200W 7 m (25')
- Head/Ballast Cable 575/1200W 15 m (50')
- Extension Cable 575/1200 W 7 m (23 ft), Schaltbau
- Head/Ballast Cable 575/1200W 7 m (25')
- Head/Ballast Cable 2500/4000W 15 m (50')
- Metal Halogen Lamp 1200 W / SE
- Stand AS-5
- Safety Cable with Carabiner